



ALL-OUT® SYSTEM

NEXT GENERATION OF HOPPER SILOS



*Product Leadership™
for a New Feed Storage Standard*

Exclusive features for ALL-OUT® silo performance

Brock reinvented the feed silo with the introduction of its next generation of hopper silos. Brock's Next Generation Feed Silo raises a new industry standard for excellence and value. Added together, the innovative features of the Next Generation Feed Silo comprise Brock's ALL-OUT® System to provide solutions for better productivity in your operation. The ALL-OUT® System solves problems producers reported to us and improves on all previous generations in feed storage.

Product Features

- **SPRING-LOCK® Lid** provides a positive, spring-aided closing action, yet is easy to open with one hand.
- **40° Roof** matches the natural incline angle of repose for stored feed to maximize usable feed storage capacity.
- **HYDROSHIELD® Weather Guard** directs moisture to drip off the silo's sidewall and keeps it off the silo's hopper and boot.
- **ACCESS PLUS® Hopper Access Door** permits easy clean out of the silo from the ground. The Door retrofits into previous Brock feed silo models too.
- **Digital WEIGH-MATIC® Scale System** uses temperature-compensated load cells to give highly accurate weights for feed stored in individual feed silos.
- **Automatic boot slide actuator system** automatically closes boot slide shut off on empty silo while opening second silo in tandem systems. Manual actuator is also available.

Product Advantages

- **SPRING-LOCK® Lid** resists wind and keeps out snow and rain. When open, the lid slides down and out of the way of feed truck's auger.
- **SPRING-LOCK® Lid and ACCESS PLUS® Door** aid in biosecurity by allowing remote silo opener location and by easing cleaning chores.
- **HYDROSHIELD® Guard** results in less water on silo hopper and boot.
- **Automatic boot slide actuator** on a tandem feed bin system helps keep birds or animals from missing a feeding.

Warranty and Service

Brock's ALL-OUT® System is backed by a generous warranty and by a worldwide network of trained technical service and distributor professionals.

For the distributor nearest you, call the International Customer Service Department at 574-658-9323.



Optional Ladder Security Door



SPRING-LOCK® Feed Silo Lid & Opener (patented)



HYDROSHIELD® Weather Guard (patented)



Sturdy Ladder System includes a convenient handrail (patented)



Optional ACCESS PLUS® Hopper Access Door (patented)



Red translucent boot transition offers highest durability and even flow

HOPPER SILOS—40° Roof & HYDROSHIELD®

| MODEL NUMBER | CAPACITY | | HEIGHT TO FILL M |
|--|----------|------------------------------------|------------------|
| | TONS | 641 KG/M ³ CUBIC METERS | |
| 1.8 meter diameter silos w/60° hopper | | | |
| 45-00601 | 2.8 | 4.44 | 3.5 |
| 45-00602 | 4.2 | 6.57 | 4.3 |
| 45-00603 | 5.6 | 8.69 | 5.1 |
| 45-00604 | 6.9 | 10.81 | 5.9 |
| 2.1 meter diameter silos w/67° hopper | | | |
| 45-00721 | 4.5 | 6.95 | 4.5 |
| 45-00722 | 6.3 | 9.83 | 5.3 |
| 45-00723 | 8.1 | 12.70 | 6.1 |
| 45-00724 | 10.0 | 15.57 | 6.9 |
| 45-00725 | 11.8 | 18.44 | 7.7 |
| 45-00726 | 13.7 | 21.31 | 8.6 |
| 2.7 meter diameter silos w/60° hopper | | | |
| 45-00901 | 7.8 | 12.11 | 4.8 |
| 45-00902 | 10.8 | 16.92 | 5.6 |
| 45-00903 | 13.9 | 21.74 | 6.4 |
| 45-00904 | 17.0 | 26.55 | 7.2 |
| 45-00905 | 20.1 | 31.36 | 8.0 |



Optional Digital WEIGH-MATIC® Load Cells



Optional Automatic Boot Slide Actuator System

| MODEL NUMBER | CAPACITY | | HEIGHT TO FILL M |
|--|----------|------------------------------------|------------------|
| | TONS | 641 KG/M ³ CUBIC METERS | |
| 2.7 meter diameter silos w/60° hopper (continued) | | | |
| 45-00906 | 23.2 | 36.18 | 8.8 |
| 45-00907 | 26.2 | 40.85 | 9.6 |
| 3.7 meter diameter silos w/60° hopper | | | |
| 45-01201 | 16.1 | 25.13 | 5.9 |
| 45-01202 | 21.5 | 33.58 | 6.7 |
| 45-01203 | 26.9 | 42.03 | 7.5 |
| 45-01204 | 32.3 | 50.49 | 8.4 |
| 45-01205 | 37.8 | 58.94 | 9.2 |
| 45-01206 | 43.2 | 67.39 | 10.0 |
| 45-01207 | 48.6 | 75.84 | 10.8 |
| 4.6 meter diameter silos w/60° hopper | | | |
| 45-01502 | 37.7 | 58.79 | 7.9 |
| 45-01503 | 46.1 | 72.00 | 8.7 |
| 45-01504 | 54.6 | 85.19 | 9.5 |
| 45-01505 | 63.0 | 98.40 | 10.3 |
| 45-01506 | 71.5 | 111.60 | 11.1 |
| 45-01507 | 80.0 | 124.81 | 11.9 |
| 45-01508 | 88.4 | 138.01 | 12.8 |



Chore-Time Brock International • A Division of CTB, Inc.
 P.O. Box 2000 • Milford, Indiana 46542-2000 U.S.A.
 Phone 574-658-9323 • Fax 574-658-9296 or 574-658-3471
 E-Mail: world@ctbworld.com • Internet: www.ctbworld.com